CrumRubber Case Study



Product	3 No. Dual Pass CrumRubber LFG		
Industry	Industrial Power Generation		
Site Location	Kildare, Ireland		
Application	Landfill Gas Cleaning to protect Power Generation Plant		
Year System Installed	2015		
Air Volume Being Treated	2,250 m³/hr		
Plant Footprint	10m x 29m		
Typical Expected Media Life	> 5 years		
Compound Being Treated	Inlet Concentration Range	Removal Efficiency	
H ₂ S	200 - 2000 ppm	70% - 90% +	
Siloxane	5 - 10 ppm	20% - 30%	



CrumRubber Case Study



Product	3 Stage CrumRubber LFG		
Industry	Industrial Power Generation		
Site Location	Kildare, Ireland		
Application	Landfill Gas Cleaning to protect Power Generation Plant		
Year System Installed	2014		
Air Volume Being Treated	36 - 45 m³/hr		
Plant Footprint	2m x 4m		
Typical Expected Media Life	> 5 years		
Compound Being Treated	Inlet Concentration Range	Removal Efficiency	
H ₂ S	1500 - 4000 ppm	70% - 90% +	
Siloxane	5 - 10 ppm	20% - 30%	



CrumRubber Case Study



Product	CrumRubber		
Industry	Industrial Wastewater		
Site Location	Cork, Ireland		
Application	Treatment of High Levels of H ₂ S from Anaerobic Digester Transfer Point		
Year System Installed	2012		
Air Volume Being Treated	400 m³/hr		
Plant Dimensions [l x b x h]	2m x 1m x 2.5m		
Volume of Media	3.6 m ³		
Typical Expected Media Life	> 15 years		
Compound Being Treated	Inlet Concentration Range	Removal Efficiency	
Odour	80,000 – 800,000 OU _E	99% +	
H ₂ S	40 - 400ppm	98% +	



CrumRubber Case Study



Product	CrumRubber		
Industry	Municipal Wastewater		
Site Location	Galway, Ireland		
Application	Pre-filter to Mónashell for Sludge Thickening Tank		
Year System Installed	2002		
Air Volume Being Treated	200 m³/hr		
Plant Dimensions [l x b x h]	1.2m Dia x 3m		
Volume of Media	2 m ³		
Typical Media Life	> 15 years		
Compound Being Treated	Inlet Concentration Range	Removal Efficiency	
H ₂ S	0 - 200ppm	70% +	





CrumRubber Case Study



Product	CrumRubber/Monashell Triple Pass Hybrid OCU	
Industry	Municipal Wastewater	
Site Location	Dublin, Ireland	
Application	Treatment of High Levels of H₂S from the Sludge Centrifuges.	
Year System Installed	2014	
Air Volume Being Treated	10,000 m³/hr	
Plant Dimensions [l x b x h]	CrumRubber [Stage 1] [7.5 m x 5 m x 3.8 m] Mónashell [Stages 2 & 3]14.8m x 5 m x 3.8 m	
Volume of Media	321 m³	
Typical Expected Media Life	> 7 years [Stage 1] 2 Years Stage [2 and 3]	
Compound Being Treated	Inlet Concentration Range	Removal Efficiency
Odour	1,044,000 OU _E	99% +
H ₂ S	50 - 505ppm (950ppm Peak)	98% +

